

CERTIFICATE OF CONFORMITY

We hereby certify that the following item complies with the features listed below.

Item

Reference	SFERACO Fig. 520
Description	BRASS BALL VALVE DRY CLEANED - from 1/4" to 2"
Manufacturer	AIRAGA - Italy
Manufacturer ref	0675

Main features

Body	Nickel-plated CW617N
Closure member	Ball Chrome-plated CW617N
Seat	PTFE
Connections	BSP - female/female
Specifications	Full bore, Anti-blowout stem from 1/2" to 2" , lever

Operating conditions

Fluids	Oxygen, argon, azote
PS	60 bar up to 1" 1/2, 40 bar from 3/4" to 1", 30 bar for 1" 1/4 , 25 bar for 1"1/2, 16 bar for 2"
TS	-20°C to +120°C

Standards

2014/68/EU Directive - DN1/4" to DN1" : Products excluded from directive (Article 4, § 3), no CE marking; DN1"1/4-2" : compatible pour gaz du groupe 1 et 2 (16 bars maxi), liquides du groupe 2, Catégorie

de risque I, marquage CE

A, CE marking

Quality management according to ISO 9001:2015

Degreased according to NF EN ISO 23208

Product guarantee

2 years

Technical Director
St-Quentin-Fallavier, France, 15 July 2024



SYVECO
107 rue du Ruisseau
38070 Saint-Quentin-Fallavier - FRANCE
+33 474 948 650 | info@syveco.com
VAT : FR 92 487 897 449